

**RUS19069**

直线循环滚柱轴承组件

带间隔元件的直线滚珠轴承 RUS

## 技术信息

## 主要尺寸和性能数据

$L_{tot}$	74 mm	total length
L	70.4 mm	
B	27 mm	宽度
H	19 mm	高度
C	42,000 N	Basic dynamic load rating
$C_0$	66,000 N	Basic static load rating
$\approx m$	0.208 kg	重量

## 安装尺寸

$L_1$	43.8 mm	Mounting dimension
$J_B$	20.6 mm	Mounting dimension
$J_L$	25.5 mm	
$H_1$	0.2 mm	
$L_4$	50 mm	minimum support length
$L_W$	10 mm	
$H_4$	15.2 mm	
$T_5$	6.2 mm	
$G_1$	M4	fixing screws top (DIN ISO 4762-12.9)
$G_1 M_A$	5 Nm	Tightening torque fixing screws
$K_3$	M3	fixing screws below (DIN ISO 4762-12.9)
$K_3 M_{Amax}$	1.8 Nm	Tightening torque fixing screws
$D_2$	3.5 mm	
	6 mm	

## Related products

VUS19069-A	Adjustment gib
UG6628, UGN6628,	suitable Guide rail
UZ6628, UZN6628,	
U FK3210, UFB4710	

