

**RUS38134**

## 直线循环滚柱轴承组件

带间隔元件的直线滚珠轴承 RUS

## 技术信息

## 主要尺寸和性能数据

|             |           |                           |
|-------------|-----------|---------------------------|
| $L_{tot}$   | 132 mm    | total length              |
| L           | 132.7 mm  |                           |
| B           | 52 mm     | 宽度                        |
| H           | 38 mm     | 高度                        |
| C           | 179,000 N | Basic dynamic load rating |
| $C_0$       | 275,000 N | Basic static load rating  |
| $\approx m$ | 1.27 kg   | 重量                        |

## 安装尺寸

|                |         |   |
|----------------|---------|---|
| $L_1$          | 84.7 mm | Mounting dimension                      |
| $J_B$          | 41 mm   | Mounting dimension                      |
| $J_L$          | 51 mm   |   |
| $H_1$          | 0.2 mm  |   |
| $L_4$          | 100 mm  | minimum support length                  |
| $L_W$          | 20 mm   |   |
| $H_4$          | 31 mm   |   |
| $T_5$          | 14.2 mm |   |
| $G_1$          | M8      | fixing screws top (DIN ISO 4762-12.9)   |
| $G_1 M_A$      | 41 Nm   | Tightening torque fixing screws         |
| $K_3$          | M6      | fixing screws below (DIN ISO 4762-12.9) |
| $K_3 M_{Amax}$ | 17 Nm   | Tightening torque fixing screws         |
| $D_2$          | 6.9 mm  |   |
|                | 6 mm    |   |

## Related products

|   |                     |
|---|---------------------|
| VUS38134-A                                | Adjustment gib      |
| UG12553, UGN12553-A, UZ12553, UZN12553-A, | suitable Guide rail |
| UFG6412, UFB7812                          |                     |

